G HUSQVARNA EZ T-REX®

G HUSQVARNA

S HUSQVARNA

VARI-GRIND EZ SL

The wood series is a single-layer

diamond tool specifically developed

for efficient initial grinding of wood.

SURFACE TEST EQUIPMENT

Part of the EZchange™ tool system.

ELITE-GRIND SGW

EZchange™ tool system.

Metal bonded tool with cross

attachment system specifically

natural stone floors. Part of the

a clean surface with efficiency and

HUSOVARNA T 10000

HUSQVARNA T 4000

4 kW, 380-415 V, 16 A,

HUSOVARNA DE 110 SH

SLURRY VACUUMS

 $0.9\,kW$, $220-240\,V$, $4\,A$, $215\,m^3/h$, $25\,kg$.

400 m³/h, 106 kg.

11kW, 380-415V, 32A, 900 m³/h, 336 kg.



HUSQVARNA BMG 2200 63 kW, 400 V, 125 A, grinding width 2200 mm, grinding disc 3x3, 3035 kg.



HUSQVARNA HTC 950 RX 15 kW, 380-415, 440-480 V, 3-phase. grinding width 920 mm, grinding disc 4×270 mm, 600 kg.



HUSQVARNA PG 830 RC 16.5 kW, 380-415 V, 3-phase, grinding width 800 mm, grinding disc 3×270 mm, 598 kg.



HUSQVARNA PG 830 16.5 kW, 380-415 V, 3-phase, grinding width 800 mm, grinding disc 3 × 270 mm, 556 kg.



HUSQVARNA PG 830 S HUSQVARNA HTC X8/HTC RX8 11kW, 380-415 V, 3-phase, grinding width 12-15 kW, 380-415 V, 3-phase, grinding width 800 mm, grinding disc 3 × 270 mm, 497 kg. 800 mm, grinding disc $3 \times 270/4 \times 270$ mm, 499/574 kg.



HUSQVARNA BMG 780 / BMG 780RC 15 kW, 400 V, 32 A-63 A, 3-phase, grinding width 780 mm, weight 487/639 kg.



HUSQVARNA PG 690 RC 12.5 kW, 380-415 V, 3-phase, grinding width 640 mm, grinding disc 3×270 mm, 598 kg.



HUSQVARNA HTC X6/HTC RX6 7.5 kW, 380-415 V, 3-phase, grinding width $600 \, \text{mm}$, grinding disc $3 \times 230/4 \times 230 \, \text{mm}$, 384/441 kg.



HUSOVARNA BMG 555 7.5 kW, 400 V, 16 A, grinding width 555 mm,



HUSQVARNA HTC 5 4.0-2.2 kW, 400-220 V, 3-phase/1-phase, grinding width 515 mm, grinding disc 3×230 mm. 122/179 kg.



HUSOVARNA PG 540 HUSQVARNA PG 510 40-22kW 400-220V 3-phase/1-phase 4.0-2.2kW, 400-220V, 3-phase/1-phase, grinding width 515 mm, grinding disc grinding width 515 mm, grinding disc 3×230 mm, 178/169 kg. 3×230mm, 133/120kg.



HUSOVARNA PG 450 2.2 kW, 230 V, 1-phase, grinding width 450 mm, grinding disc 3 × 180 mm, 109 kg.



HUSOVARNA BMG 444SC 2.2 kW, 230 V 16 A, grinding width 444 mm, 132/135 kg. Fixed speed/speed control.

SINGLE DISC GRINDERS

HUSOVARNA PG 690

12.5 kW, 380-415 V, 3-phase, grinding width

640 mm, grinding disc 3×270 mm, 502 kg.



HUSOVARNA PG 400 $4\,\text{kW}, 400\,\text{V}, 3\text{-phase}, \text{grinding width}$ 400 mm, 115 kg.



HUSQVARNA PG 400 PETROL Grinding width 400 mm, 140 kg.



HUSQVARNA PG 280 3-2.2 kW, 400-220 V, 3-phase/1-phase, grinding width





HUSQVARNA HTC 270 EG 2.2 kW, 230 V, 1-phase, grinding width 270 mm, 103 kg.





HUSQVARNA BG 250 5.5 kW, 400 V, 3-phase, grinding width 250 mm. 146 kg.



G HUSQVARNA RAVAGER s EZchange™ tool system with PCD Developed for creating a bushsegments for aggressive removal of hammered surface or to expose large various types of coatings, resulting in



G HUSQVARNA ELITE-GRIND EZ-SERIES

EZchange™ tool system consisting of six different tool types to efficiently grind and prepare concrete floors of varying hardness. Achieve smooth and exposed surfaces with a consistent scratch pattern.



50 mm/10" bolt-on grinding discs for

for Husqvarna BGS/BG 250.

S HUSQVARNA VARI-GRIND **G** HUSQVARNA EZ-SERIES GRINDING DISCS

EZchange™ tool system of concrete high removal applications. Designed grinding tools ideal for users looking for the best price-performance ratio. Available in three bonds and three arit sizes.



TACTI-GRIND EZ-SERIES EZchange™ tool system for concrete of selection. Available in one bond with three grit sizes.



The Husqvarna EZchange™ tool holder range is designed to maximise productivity while minimising downtime. The tool holders are engineered to support the tools and make the tool-change process hassle-free.



HUSQVARNA BOT3000E FRICTION TESTER A portable fully-automatic instrument to test slip resistance of floors. Measures for example Ra, Rz, Rmax. both SCOF and DCOF in both

wet and dry conditions.

ICRI PROFILE

CONCRETE SET

concrete samples

A set of 10 different real

according to the globally

FLOOR GROUTING

For pore filling of pin-

concrete surfaces:

holes and micro cracks in

GM 3000 201, GM+ 91.

SYSTEM

accepted ICRI specifications

corresponding with CSP 1-10

FLOOR TREATMENT PRODUCTS



PLASTIC CHIPSET

ICRI specifications.

FLOOR HARDENING

For making concrete mor

wear resistant and dust-free-

CURE (K) 201, CURE (L) 201.

SYSTEM

A chipset with 10 different

HUSQVARNA RHOPOINT PS10 - ROUGHNESS TESTER IQ - GLOSS AND DOI METER GLOSS CHECKER A mobile surface roughness A powerful mobile surface tester. Measures 31 parameters, quality tester. Measures Gloss, specifically developed for DOI and HAZE.

Mohs scale.

FLOOR PROTECTION

For protecting the surface

51/101, Topical Guard 201,

Topical Guard Color LG 201

Topical Guard Color DG 201.

SYSTEM



A portable gloss meter











SYSTEM For cleaning and maintenance: against stains: Premium Guard Clean & Protect 51. WB 51/101, Premium Guard SB





G HUSQVARNA ELITE-POLISH EP D

This high-performing concret polishing tools series performs on all types of concrete. EZchange" attachment system.



RESIN TOOLS FOR POLISHING

G HUSQVARNA

ELITE-POLISH ET D

For the efficient removal of

bonded tools. EZchange™

ELITE-POLISH EF W/D

Premium resin technology with an

optimised flexible design to achieve

a high level of polishing and gloss.

EZchange™ attachment system.

attachment system.

G HUSQVARNA

G HUSOVARNA

S HUSQVARNA VARI-POLISH VP W/D

S HUSQVARNA VARI-POLISH VS D

B HUSQVARNA

TACTI-POLISH TT W

Polishing pucks optimal for the

transition process. Suitable for wet

FLITE-POLISH EX D

EZchange™ attachment system.

Resin bond polishing pads can be chosen for high-end polishing. Grit

range from 50 to 3.000. Universal

Specially designed for sanding when

restoring wooden floors. Universal

VELCRO® brand attachment for use

on any machine. Use together with

Husqvarna Foamflex pads

VELCRO® brand attachment.

scratches and a safer transition

when shifting from metal to resin

G HUSOVARNA ELITE-POLISH EB/EM W/D PADS

Diamond-impregnated maintenance pads, ideal for cleaning polished concrete floors. Fits both auto scrubbers and grinding machines, Velcro® or EZchange™ attachment system.



S HUSQVARNA VARI-POLISH VT W/D

Serves as the ideal starting point when Top-of-the line tools for dry grinding the surface is too rough to begin and polishing of natural stone surfaces. directly with polishing tools. Available for wet or dry applications, Universal VELCRO® brand attachment.



S HUSQVARNA VARI-POLISH VF D

Optimal for polishing concrete and overlays or screed. It's the best troubleshooting product for all kinds



B HUSQVARNA

TACTI-POLISH TP D Entry-level polishing pucks for stress-free polishing in a wide range of grit sizes. Universal VELCRO® brand attachment.



G HUSQVARNA ELITE-POLISH EO D

 $\mathbf{D} = Drv$

W = Wet

A high-performance, resin-bonded transitional tool for cementitious applications. Universal VELCRO® brand overlays. Universal VELCRO® attachment for use on any machine



S VARI-POLISH VC D Diamond-infused triangular pads designed for precision edge grinding of corners leaving no untouched areas. Universal VELCRO® brand attachment for use on any machine.



HUSQVARNA W 70

 $200\,m^3/h$, $34\,kg$.

1.2 kW, 220-230 V, 5A,

HUSOVARNA S11

1.2 kW, 220-230 V, 16 kg.

HUSQVARNA W 70 P 1.2 kW, 220-230 V, 8 A, 200 m³/h, 44 kg.



HUSOVARNA T7500

FLECTRIC-POWERED HUSQVARNA DE 120 H

480 m³/h, 39 kg.

2.2 kW, 220-240 V, 15 A,

5.5 kW, 380-415 V, 16 A, 600 m³/h, 206 kg.

HUSQVARNA DE 120 H PACE 480 m³/h, 41 kg.



HUSOVARNA HTC D80

HUSQVARNA DE 110i H Weight 26 kg. Husqvarna BLi 36 V

PRE SEPARATORS

HUSOVARNA C 5500

76 mm, 100 l, 67 kg.



HUSQVARNA HTC D60 7.5 kW, 230-400 V, 16.7 A, 700 m³/h, 272 kg. 5.5kW, 230-480V, 15A, 530 m³/h, 179 kg.



HUSQVARNA DE 110 H 1.1 kW, 220-240 V, 5 A,



HUSQVARNA C 3000 63 mm, 37 l, 27 kg.

AIR CLEANERS



HUSQVARNA W 250 P 1.2kW, 220-230V, 7A,





HUSQVARNA A 1000 0.285 kW, 220-230 V,