

# BATTERY-POWERED HUSQVARNA K1 PACE

7.2/7.4 kg, blade size 300/350 mm, cutting depth 121/145 mm. PACE 94V battery system.





# HUSQVARNA K 540i

4.17 kg, blade size 267 mm, cutting depth



**HUSQVARNA K 970 SMARTGUARD** 

94cc, 4.8kW, 11.9/12.8kg, blade size 350/400mm, cutting depth 125/155mm.



HUSQVARNA K 770 DRY CUT 74cc, 3.7kW, 12.0kg, blade size 305mm,

cutting depth 123 mm

HUSQVARNA K 1270 RAIL

119 cc, 5.8 kW, 20.5/21.2 kg (incl. RA10), blade size 350/400 mm, cutting depth 118/145 mm.



### HYDRAULIC-POWERED **HUSQVARNA K 2500**

150 bar/40 l/min, 5.2 kW, 8.3 kg, blade size 400 mm, cutting depth 145 mm



# ILLT.

# HUSOVARNA K 7000 RING

230/400 V. 5.5 kW (3-phase)/3 kW (1-phase) 13.1/12.4 kg, blade size 350/425 mm, cutting depth 270/325 mm.



# 

BATTERY-POWERED
HUSQVARNA K 1 PACE RESCUE 7.9 kg, blade size 350 mm, cutting depth 145 mm. PACE 94V battery system.



PETROL-POWERED HUSQVARNA K 1270

119 cc, 5.8 kW, 13.3/13.7 kg, blade size 350/400 mm, cutting depth 118/145 mm.



PETROL-POWERE HUSQVARNA K770/ K 770 WITH OILGUARD

74 cc, 3.7 kW, 10/10.1 kg, blade size 300/350 mm, cutting depth 100/125 mm.



PETROL-POWERED HUSQVARNA K 970 RING

94cc, 4.8kW, 13.8/14.2kg, blade size 370/430 mm, cutting depth 270/325 mm.



HUSQVARNA K 970 RESCUE

94cc, 4.8kW, 11kg, blade size 350 mm, cutting



### AIR-POWERED HUSQVARNA K 40

 $7\,kp/cm^2$ ,  $3.2\,kW$ ,  $9.9\,kg$ , blade size  $350\,mm$ , cutting depth 125 mm



# HUSOVARNA K 7000 CHAIN

230/400 V. 5.5 kW (3-phase)/3 kW (1-phase) 9.1 kg, bar size 450 mm, cutting depth 450 mm.



# BATTERY-POWERED HUSQVARNA K 1 PACE RAIL

7.9 kg, blade size 356 mm, cutting depth 133 mm. PACE 94V battery system.



**HUSQVARNA K 1270 SMARTGUARD** 

119 cc, 5.8 kW, 15.1 kg, blade size 400 mm, cutting depth 118/145 mm.



HUSQVARNA K 770 SMARTGUARD

74 cc, 3.7 kW, 10.8/11.1 kg, blade size 300/350 mm, cutting depth 100/125 mm



HUSQVARNA K 760 CUT-N-BREAK 74 cc, 3.7 kW, 11.1 kg, blade size 230 mm,

cutting depth 400 mm



**HUSQVARNA K770 RESCUE** 

 $74\,cc,\,3.7\,kW,\,9.6\,kg,\,blade\,size\,300$  mm, cutting



### ELECTRIC-POWERED HUSQVARNA K 7000

230/400 V, 5.5 kW (3-phase)/3 kW (1-phase), 9.8 kg, blade size 400 mm, cutting depth



# HUSOVARNA K 4000

230/120/110V. 2700/1800/2200W. 8.5 kg (incl. Vac attachment 1 kg), blade size 350 mm, max. cutting depth 125 mm.



# BATTERY-POWERED HUSQVARNA K 535i

3.5 kg, blade size 230 mm, cutting depth 76 mm. BLi 36V battery system.



HUSQVARNA K 970

94 cc, 4.8 kW, 11/11.6 kg, blade size 350/400 mm, cutting depth 125/155 mm.



HUSQVARNA K770 VAC

74 cc, 3.7 kW, 11.0 kg, blade size 305 mm, cutting depth 123 mm.



### PETROL-POWERED HUSQVARNA K 970 CHAIN

 $94\,cc,\,4.8\,kW,\,9.7\,kg,\,bar\,size\,350\,mm,\,cutting$ depth 400 mm.



# HUSQVARNA K 3600 MK II

150bar/401 min. 4.3kW. 8.3kg. blade size 370 mm, cutting depth 270 mm



### ELECTRIC-POWERED HUSQVARNA K 7000 SMARTGUARD

230/400 V, 5.8 kW (3-phase)/3 kW (1-phase), 5.1 kg, blade size 400 mm, cutting depth



## HUSOVARNA K 4000 CUT-N-BREAK 230/120/110V. 2700/1800/2200W.

8.9 kg, blade size 230 mm, cutting depth construction materials.

FLITF-level blades with Exo-Grit segments for a smooth, efficient cut - even in reinforced concrete. Diameters 300-400 mm in several versions optimised for different materials.



## B HUSQVARNA TACTI-CUT S 35 S BAT Providing a good balance between performance

**G** HUSQVARNA ELITE-CUT

and price in all cutting operations.



# G HUSQVARNA CUT-N-BREAK BLADE

For the K 760 / K 4000 Cut-n-Break FLITF-level blades with a segment shape that produces excellent cutting characteristics and performance Available in three hardness levels



# B HUSQVARNA TACTI-CUT

TACTI-level blades optimised for less intensive professional cutting in most materials. Diameters 300 – 400 mm in several versions optimised for different materials.



# S HUSQVARNA RESCUE BLADES

Blades with brazed diamond technology for allround free cutting in materials such as concrete rubber, brick, metal and steel, etc. Suitable for rescue applications. Diameters 300 - 400 mm.



# S HUSQVARNA VARI-RING

VARI-level ring saw blades available in three hardness levels. Diameters 370 mm and 425 mm.



# G HUSQVARNA ELITE-CHAIN 450 MM/18"

A range of professional, premium and quality chains for sawing in reinforced concrete and other



# S HUSQVARNA VARI-CUT

VARI-level blades tailored for demanding professionals working on a variety of quick jobs. The new increased segment height provides higher speed and extended blade life Diameters 300 – 400 mm in several versions optimised for different materials




## B HUSQVARNA TACTI-CUT S 35 S PACE™

Providing a good balance between performance and price in all cutting



### G HUSQVARNA ELITE-RING

ELITE- level ring saw blades designed for optimal cutting speed, even in the hardest reinforced concrete. Three hardness levels. Available in Pre-Cut version with 6.0 mm-wide segments. Diameters 370 and 425 mm.



G HUSQVARNA ELITE-CUT S 35 S BAT Providing maximum cutting speed and wear resistance in all heavy cutting jobs.



# G HUSQVARNA ABRASIVE DISCS

S Top-grade abrasive discs that can cut practically any material, such as stone, steel and railway rail. Diameters 300-400 mm.



# **G** HUSQVARNA ELITE-GUIDE BAR 450MM/18"

Guide bars developed to be the optimal choice of cutting equipment for any Husqvarna concrete chainsaw. Fits on both new and older models of Husavarna concrete chainsaws



# S HUSQVARNA VARI-CHAIN 450 MM/18'

Ideal for demanding professionals, this is a chain that delivers high cutting speed in various allround construction applications.



HUSOVARNA KV 7 Cutting trolley designed for K 760 and K 770. Water tank 13.31.



### HUSOVARNA KV 9/12

Cutting trolley designed for K 970 and K 1270. Water tank 13.31.

## **ACCESSORIES FOR POWER CUTTERS**



# RATTERY-POWERED

**HUSQVARNA WT 15i** 

HUSOVARNA PIPE CLAMP KIT

cuts in concrete and iron pipes

For use with Husqvarna K 970 Ring and Chain and K 7000 Ring and Chain. A convenient

accessory for producing straight, precise

Compact and easy-to-use water tank with electric pump. Has a capacity of 15 litres and allows for continual cutting for 45 minutes. Battery-powered, 36 V BLi system.



## HUSOVARNA WT 10 MP

Pressurised water tank, superb when there's no water supply. Pump a few times for the required work pressure. Hose included for connecting to the machine's wet cutting kit. Holds 10 litres.



## **HUSOVARNA RA 10**

HUSQVARNA K 3000/K 4000 VAC ATTACHMENT Cutting attachment for the K 1260 Rail,  $5.3\,\mathrm{kg}$ .

# Ideal dust collection enables you to cut without water. Fits K 3000 Wet/Vac and K 4000.

# **EQUIPPED FOR THE JOB**

SmartGuard™ is a line of innovative protective equipment, with features that help you do your job efficiently and in control of your operational safety - without compromising on your comfort or mobility.



### HUSQVARNA SMARTGUARD™ HELMET PE 10 H

A robust and lightweight helmet with a special chin guard aiming to increase protection of the operator's face. Complete with visor, hearing protection and room for an anti-dust mask and personal eye protection.

### HUSQVARNA SMARTGUARD" BLADE COVER

Reduces the risk of severe injury from kickbacks and promotes correct technique by guiding the user to the cutting zone.



## HUSQVARNA SMARTGUARD™ JACKET PE 10 J

The SmartGuard™ jacket is made with reinforced material aiming to increase protection of the operator's neck and chest. The jacket offers comfortable movement, high visibility according to EN20471 class 2. Removable sleeves, smart pockets and ventilation. Sizes S-XXL.



