## CONCRETE CORE DRILLS, DRILL MOTORS WITH STANDS AND DRILL STANDS



HUSQVARNA DM 540i

1350 W, recommended drill diameter 015-75 mm (100 mm with drill stand), 49 kg. BLi 36V battery system.



HUSQVARNA DM 1 PACE 2.5 kW, recommended drill diameter 25-400 mm, 17.3 kg (incl. battery).



**HUSQVARNA DM 700** 

6000/3000 W 3-phase/1-phase recommended drill diameter 80-600 mm.



HUSQVARNA DM 430

3200 W, 1-phase, recommended drill diameter 100-450 mm. 15.5 kg.



**HUSOVARNA DM 400** 

3200 W, 1-phase, recommended drill diameter 55-350 mm. 14 kg



HUSQVARNA DM 370

3200 W, 1-phase, recommended drill diameter 25-250 mm, 14 kg.



HUSOVARNA DM 406 H

120/230/340/580/980/1400 rpm. recommended drill dia meter 0-650 mm, 16 kg.





**HUSQVARNA DM 220** 

1850 W, 1-phase, recommended drill diameter 150 mm, handheld 80 mm, 7.5 kg



2000 W, 1-phase, recommended drill diameter 25-100 mm. 6.4 kg.



DIAMOND CORE DRILL BITS

ELECTRIC-

10.5 kg

HUSOVARNA DMS 160 AT 1550 W,1 phase max Ø 120 mm





DS 900

travel length 950 mm, 24 kg.

685 mm, 16 kg.





S HUSQVARNA ELITE-DRILL TW AND **VARI-DRILL TW SERIES** 

ELITE-DRILL TW series is specially designed for battery-powered and low-powered handheld drill motors Experience a faster and smoother drilling operation with quick and precise start. ELITE-DRILL TW is a range of thin walled drill bits for wet drilling and the new ELITE-DRILL DRY series is optimised for dry drilling. Diameters 10-100 mm



HUSQVARNA ELITE-DRILL SERIES

Gold level drill bits delivering smooth, fast drilling in demanding applications. Available for various materials like heavily reinforced concrete, hard aggregate and abrasives. Diameters 92-350 mm.



HUSQVARNA DS 150 Ø 150 mm, travel length 495 mm, 15.5 kg.



## MUSQVARNA VARI-DRILL

Silver level drill bits with great performance and durability in heavy duty applications, Diameters from 18-300 mm in two versions depending on the application. 1 1/4"



## III HUSQVARNA TACTI-DRILL

Bronze level drill bits with a good price/ performance value for non intensive use in heavier applications. Diameters from 52-300 mm, 11/4" connector.





HUSQVARNA DS 50 COMBI

Ø 300 mm, travel length 1090 mm, 21 kg.



HUSQVARNA DS 50 GYRO Ø 350 mm, travel length 670 mm, 56 kg.



HUSQVARNA DS 40 GYRO Ø 150 mm, travel length 600 mm, 30 kg.

## HUSQVARNA VARI-DRILL DRY

Lightweight drill bits for dry indoord rilling by specialist professionals. Two versions available. Vacuum-brazed segments for drilling tiles and natural stone. Dia meters 5-85 mm. Laserwelded segments for drilling concrete, bricks, and cement blocks. Diameters 37-200 mm

