

QuickSeam™ Splice Tape



1. Description

The Firestone QuickSeam™ Splice Tape 76 mm (3") wide is designed for field splicing GeoSmart™ EPDM membrane panels.

2. Preparation

The Firestone GeoSmart™ EPDM surfaces must be prepared with QuickPrime™ Plus, using a solvent resistant brush or QuickScrubber™. Use of other products is not allowed. Restore the tape to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

The 76 mm (3") wide tape is used for splicing standard seams. Refer to the Firestone guidelines for specific installation instructions.

4. Coverage

In accordance with length of seam. Adjoining QuickSeam Splice Tapes require an overlap of 25 mm and a QuickSeam FormFlash cover patch.

5. Characteristics

Physical

- Excellent moisture resistance
- Excellent resistance to heat and cold, UV radiation and ozone
- Excellent green tack

Technical

- Base Rubber polymers
- Color Black
- Solvents None
- Solids 100%
- State Cured
- Thickness 0.6 mm ± 0.1 mm

6. Packaging / Storage / Shelf Life

Width (mm)	Length (m)	Packaging	Part number
76.2 (3")	30.5 (100')	6 rolls/carton	W56RAC1603

Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life: 12 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.